



Metal Clad

WIRING ACCESSORIES





www.**bgelectrical**.uk



Metal Clad Wiring Accessories

Metal Clad wiring accessories are made from a rugged scratch resistant steel with a durable powder coated finish, ideal for use in commercial and industrial environments.

The range comprises 10AX switches, 13 Amp sockets, fused connection units and RCD protection. All accessories are supplied with a multiple knock-out metal box, making them extremely versatile accommodating a variety of wiring routes.

IN THE RANGE

USB Sockets	116
Switches & Sockets	117
RCD Protection	117
45 Amp Switches	118
20 Amp Switches	118
FCU's	119
Blank & Euro Modules	119
Telephone Outlets	119
Key Controlled Socket	120
Surface Mounting Boxes	120



BG Electrical products are guaranteed against faulty materials and workmanship for a period of 25 years from date of delivery.

Features & Benefits



13 Amp Switched Socket with USB Charger 2x Outlets 3.1A

Ideal for charging iPad, iPhone, tablets, mobiles, cameras and more

- 2x Type A USB sockets 3.1A total output, 5V
- Twin earth fitted as standard
- Terminal capacity 3x 2.5mm², 3x 4.0mm² & 2x 6.0mm²
- 10 year guarantee



MC522U3

Product Code	Description	Inner Carton	Outer Carton
MC522U3	Double + 2x USB (3.1A)	5	50

LUCECO ACADEMY In association with

EV CHARGE POINT **PREPARATION** TRAINING AND CPD COURSE



18TH EDITION - AMD 2

20 Amp 16AX Plate Switches

- · Manufactured to BS EN 60669-1
- Mounting box with 1x 20mm knockouts in each side and rear face
- Terminal capacity 4x 1.0mm², 4x 1.5mm² 2x 2.5mm² & 1x 4.0mm²
- · Backed out captive screws for easy installation



MC544

Product Code	Description	Inner Carton	Outer Carton
MC512	Single, 2 way	10	50
MC513	Intermediate	10	50
MC542	Double, 2 way	10	50
MC543	Triple, 2 way	10	50
MC544	Quadruple, 2 way	5	25



13 Amp Socket Outlets

- Manufactured to BS 1363 part 2
 Terminal capacity 3x 2.5mm², 3x 4.0mm² & 2x 6.0mm²
- Single mounting box with 1x 20mm knockouts in each side and rear face
- · Colour coded terminals with backed out captive screws for easy installation

Inner


Carton

10

10

50

25



MC522



13 Amp RCD Protection

- · Maximum load 3120 watts 240V A
- · Manufactured to BS 7288:2016
- Terminal capacity 3x 2.5mm², 3x 4.0mm² & 2x 6.0mm²

Single DP socket, switched

Double DP socket, switched

Single socket, unswitched

Double socket, unswitched

- · Earth terminal in mounting box
- 30 mA trip speed 40ms
- Mounting box with 1 x 20mm knockouts in each side and rear face
- · Latching type

Product

Code

MC522

*For information on the 2 types of RCD, please see page 12





MC554RCD

25
50

Round Pin Socket Outlets

- Manufactured to BS 546
- Supplied with surface mounting box
- Mounting box with 1x 20mm knockouts in each side and rear face





MC599



MC529

Product Code Description Carton Carton MC528 Single, 2 Amp, unswitched 50 MC529 Single, 5 Amp, unswitched 10 50 10 50 MC599 Single, 15 Amp, switched

45 Amp Double Pole Switches

- Double pole switches to BS EN 60669-1
- Single mounting box with 1x 20mm knockouts in each side and rear face
- Cooker control units manufactured to BS4177
- L & N terminal capacity 4x 4.0mm², 3x 6.0mm² & 1x 16.0mm²

Double plate with power indicator

Single plate with power indicator





MC574

Product Code	Description	Inner Carton	Outer Carton	
MC570	Cooker control unit and socket with power indicator	5	35	

10

50

20 Amp Switches

MC574

Metal Clad | Wiring Accessories

- · Manufactured to BS EN 60669-1
- Mounting box with 1x 20mm knockouts in each side and rear face
- Terminal capacity 3x 2.5mm² & 1x 4.0mm²



MC531

Product Code	Description	Inner Carton	Outer Carton
MC531	Double pole switch with power indicator and optional flex outlet	5	25

13 Amp Fused Connection Units

- Manufactured to BS 1363 part 4
- Mounting box with 1x 20mm knockouts in each side and rear face
 Terminal capacity 3x 2.5mm², 2x 4.0mm² & 1x 6.0mm²
- · Removable flex outlet blank
- · Colour coded terminals with backed out captive screws for easy installation
- Flush LED power indicator
- · Cable entry with cord grip



MC551F



MC552F

Code	Description	Carton	Carton	
MC550F	Fused Connection Unit with optional flex outlet	10	50	
MC551F	Fused Connection Unit with power indicator and optional flex outlet	10	50	
MC552F	Fused Connection Unit with optional flex outlet	10	50	

Blank and Euro Module Plates

Description

Single, blank plate

Double, blank plate

Euro Module, 1 module - square


Euro Module, 2 module - square

Euro Module, 4 module - rectangular

- Not supplied with surface mounting box
- Manufactured to BS 5733



14	11	"	10	J



MC5EMS2

Telephone and Data Outlets

- Telephone and data products are supplied in Euro Module format as a kit of components separate front plate, module and mounting box
 Mounting box with 1 x 20mm knockouts in each side and rear face

Telephone master, single, screw terminals

Telephone master, double, screw terminals

RJ45 data outlet socket, single

RJ45 data outlet socket, double

Telephone secondary, single, screw terminals

Telephone secondary, double, screw terminals

Shuttered sockets

Product Code

MC5BTM1

MC5BTM2

MC5BTS1

MC5BTS2

MC5RJ451

MC5RJ452

Product Code

MC504

MC505

MC5EMS1

MC5EMS2

MC5EMR4



Carton Carton

50

25

200

100

100

10

20

10

10

Carton

FM

EM

EM EM

EM

EM



MC5BTM2



13 Amp Double Pole Key Controlled Socket Outlet

- Manufactured to BS 1363-2, BS EN 60669-1
- Mounting box depth 47mm
- Terminal capacity: 3 x 2.5mm², 2 x 4mm², 1 x 6mm²
- · Lockable socket, supplied with two keys
- · Double pole switch



MC5SKYSWSW


Product Code	Description	Inner Carton
MC5SKYSWSW	13 Amp, double pole key controlled socket outlet	EM

Surface Mounting Box

- Rugged, scratch resistant metal boxes suitable for everyday use in commercial and industrial environments
- · Manufactured in heavy gauge steel for extra safety
- Multiple knock-out mounting box
- Earth terminal fitted as standard



Product Code Description		Inner Carton	Outer Carton
MC501	Single	10	100
MC502	Double	5	50
MC503	Box for 6-8 module Grid configurations	5	25



Euro Module Range Extension

Quick & Easy Installation

A flexible solution of power, data, telephone, television and audio combinations to suit the wide ranging needs of the customer.

- Select the desired combination of front plate and module(s)
- · Simple installation, wire the module through the front plate aperture then click the module into place
- Modules of mains and extra low voltage rating must not be fitted to the same front plate aperture Ref. BS 7671:2008

See page 53 & 56



MC5EMS1







Module(s)

EMNSTVW



Nexus Grid Range Extension

Quick & Easy Installation

A customisable selection of power Grid modules that provide a seamless appearance with the associated wiring accessories.

- Firstly, screw the Grid frame to the mounting box and wire
- · Then slot the module on to the frame and click into place
- · Finally, fit the finished plate


See page 44, 48 & 49

Front Plate















Marie 1

HEAD COPPORT Break to be Stage for the last of the

Lames pls, Charte Marie IES Fisher Street, Landon Brighard, MT4/IS, N

Office United Sections

Tel -441 (\$110 100 100 Breed at party

Lancace pla Lancace Description Carties Bafferi Petr'i, Teleni Bugotta, Englani, 172380

THE PARTY

Brook & sales Busenamen

100

Briefell, polysoftensesson

1000

Tellucia dospo en 16. Bristo escuedar de propieto de la composición del composición de la composición

Heustedustes LTD Criticismins Int BISIS Morell Barriero (SPRA)

MEASURE RANGE BURNISHES

THE LAST COURSE SHAPE Briefli Imm, Advertigence com

Lucien Midde Bed P250 Belg-188, Often 342 PO Bloc Divings, DAVIDS. Dalled USA

MAIN PAGENCE

- NO. WO.

The same payment from the con-Fred and a Continuous some No. 1639, January Front Number including Park, Juneary Employ China, No. 200231

новелоска Глей 10 уживания

Marin Marin College

Free to print the section

MESCOO BILLET IN AMERICA.

The sale projection and a Front vertex Maintenance Representations An Library Contents of Children 201 Call Field Ran Agentin San Part or Course Course NA, Marian GP 88678

TROUBLESS MARKS TO

Tel: 100 pg 1002 220 120 From technical appointing about the court

Unes open Minnley in Printer 6.X has in figure, with an averaginarie operation calculate throat house.

















