



Technical Data

Battery Smoke Detector

Product Description

Description

The BG long life smoke detector is versatile and can be used in a wide number of applications. The sealed in lithium battery cell means that the battery never needs to be changed and will continue to function for 10 years after installation. After 10 years, it will sound an end of life warning so that you know it needs to be changed.

Function

Photoelectric Sensing Technology

Installation Location

Can be used anywhere around the home particularly in bedrooms, living rooms and hallways

Application

Indoor

Operating Temperature

0°C to +40°C

Standard

BSI certified to BS EN14604:2005

Product Images



SDLLSM

Technical Specification

	SDLLSM
Sensor	Photoelectric Sensing Technology
Button Test	Combined Test/Hush button, allows regular testing of alarm function and can be used to temporarily silence nuisance alarms
Audible Alarm	85 dB at 3 metre
Ramp Up Horn	Allows sound emitted during test sequence to be reduced to a more acceptable volume for the user
Alarm Sounder	Electronic piezo-electric sounder (T4 pattern sound - four pulses - space - four pulses)
Supply Voltage	Sealed in battery
Humidity Range	Up to 90% relative humidity (RH) non-condensing
Alarm Dimensions	116 x 72 x 40 mm
Alarm Weight	170g
Warranty	10 years